

Miniload

Automatedwarehouses for boxes

EASY FIT STORAGE
SOLUTIONS



Automated warehouses for boxes

Storage processes have become a strategic element in supply chain management and, therefore, in the creation of value in business.

In addition, the integration of automated systems in handling processes has a direct impact on the productivity of organizations, reducing costs and improving services in the supply chain.

This increase in productivity is even more apparent when automatic stacker cranes (miniload) are used in a warehouse for boxes. With these cranes, full use can be made of the height and width of space in the warehouse and the stored product brought closer to the operator, ensuring an efficient system for the preparation of orders.

Mecalux Group has more than 50 years' experience in the installation of storage systems and equipment for all sectors of the economy, using the most advanced technologies in industry.



Table of contents

Characteristics ofautomated warehouses for boxes 4

Basic components **6**
Stacker crane.....6
Racking 8
Picking and handling area 9
Management system 9
Load unit 10
Control and safety systems 10
Optional equipment 11

Optional elements 12
Loadunits 14
Extraction systems 16
Models of stacker cranes 18
Single or double depth .....20 One
or more aisles .....22 One
stacker crane per aisle .....22 One
stacker crane for several aisles 23
Several stacker cranes per aisle 24
Picking and replenishment positions 26
Role as buffer 38
Working temperatures 39
Combination with other warehouse systems 40
Support equipment for the preparation of orders 48
Automatic classification sorter 50

Warehouse management system 54

The advantages of automation 56



Automated warehouse system for boxes that combines racking, stacker cranes, conveyors, and warehouse management software as a single product.

Characteristics of automated warehouses for boxes

Optimal for storage and picking in accordance with the "product-to-man" principle.

These warehouses consist of one or more aisles with racking on both sides for storing boxes or trays, with a stacker crane moving up and down each aisle, moving and depositing boxes in their location. The picking and handling area, which consists of conveyors where stacker cranes deposit loads extracted from the racking, is located at one end or next to the racking. The conveyors carry each box to the operator and once they have done their work, return the box on the stacker cranes to be placed in its correct position in the racking.

The whole system is directed by a management software program that records the location of all goods in the warehouse and keeps a real-time inventory. As a result of its extraordinary ability to adapt, it can be integrated into any production or warehouse process.





Advantages:

-Itautomatesthe entry and exit of products.

- It saves warehouse space.
- It eliminates the need for manually-operated turret trucks and averts accidents as a result of handling errors


-Iteliminateserrorsresultingfrom manual handling in the warehouse.

- It monitors and updates inventory management.
- It can operate365 days a year.
- Itsignificantlyincreasescapacity forcustomer service.
- It has a shor treturn on investment period (ROI).

Basic components of automated warehouses for boxes

Automated warehouses for boxes consist mainly of the following elements:

- Stacker crane
- Racking
- Picking and handling area
- Management system
- Load unit
- Control and safety systems
- Optional equipment



Stacker crane

A robot that locates and removes boxes on racking, and carries and deposits them on the conveyor in the header of the warehouse.


The crane can perform two movements: lateral, over the rail along the aisle and vertical, to place boxes on the different levels of racking as required. Lateral movements to extract and deposit boxes are performed using the extraction system located in the lifting cradle.




Components of the stacker crane
This robot, which can handle and store goods, consists of various elements that comprise an integrated unit. It moves around on rails embedded into the floor, with its upper section guided by a profile attached to the racking.

The correct position of the stacker crane is controlled using laser telemeters. Communication is via cable-free devices using infrared signals (communication photocells). For its power supply, it uses open fixed lines and glide plates.

1. Top guide base
2. Column
3. Bottom guide base
4. Remote electric box
5. Cradle and extraction system
6. Drive engine
7. Elevator motor
8. Laser telemeter
9. Cable-free communications equipment
10. Line for power supply
11. Lower track 12. Upper track 13. End-of-aisle stop






Top guide base (1) and upper track (12)



Cradle or mobile lifting frame (5)



Lower track (11), hydraulic adjustment stop (13) and telemeter (8)



Bottom guide base (3), elevator motor (7) and power supply (10)





Racking

Designed for storing boxes in height, the racks are perfectly suited for the movement of the stacker crane. Their design allows for more efficient use of space and increased warehouse capacity.









Picking and handling area

This areais located next to or in front of the racking. This is where the mechanical movements needed to bring the boxes closer to the operator or stacker crane occur, so that they can be collected and returned to their position in the warehouse.

This area consists of a series of conveyors that facilitate communication between work stations and stacker cranes, speeding up the entry and exit of goods from the warehouse.

There are two conveyor systems for b oxe s:
- Roller conveyors
- Belt or band conveyors

Management system

This system runsall the warehouse operations, making the most of the time and the use of warehouse space.

Its ease of use and integration make it a warehouse management tool that is in perfect symbiosis of the ERP of the client.

This software simplifies the management of all storage processes, and enables simple access to all information in real time.

It also keeps an ongoing, up-to-date inventory of all the goods in the warehouse.







Plastic box

Load unit

Automated facilities can also be made to store plastic, metal, or cardboard boxes. The most common plastic boxes are euroboxes that measure 16" x 24" or 24" x 32", at normal height.

The ideal load unit in automated warehouses for boxes is determined based on the product to be stored.





Cardboard box

Control and safety systems

A powerful and experimented control software program, together with various mechanical and electronic devices, executes movements in a safe and accurate manner.

Steel mesh enclosures have been erected in open areas to prevent contact by operators with moving elements that could pose a risk. Access doors are connected to the control system, so that the machines stop when the doors are open.







Optional equipment

Othersupportequipmentcan also be included, such as:

- Barcode readers
- Report and label printer
- Scales
- Pick to light and put to light devices, etc.



Optional elements in an automated warehouse for boxes

Automatedwarehousesfor boxes allowfor different options accordingto the requirements of each facility. The options chosen will be in response to specific requirements to be met.



1. Load units
2. Extraction systems
3. Models of stacker cranes
4. Single or double depth
5. One or more aisles
6. One stacker crane per aisle
7. One stacker crane for several aisles
8. Several stacker cranes per aisle
9. Picking and replenishment positions
10. Role as buffer
11. Working temperatures
12. Combination with other warehouse systems
13. Support equipment for the preparation of orders
14. Automatic classification sorter

All of the above are suitable for:

- Heights of up to 66'
- Loads of up to 220lb per box
- Variable lengths


MECALUX



1

Load units

Automated warehouses for boxes are built for different load units. The most common of these load units are as follows:







Plastic box with dividers

Eurobox (16" x 24")

- The most common model, due to its measurements and construction.
- Different heights that are suitable for the goods and the volume stored are available.
- The bases of the boxes can be smooth or reinforced, depending on their weight and use.
- Optional lid to protect the product.
- Option to incorporate subdivisions to store various SKUs without mixing them together.

Eurobox (24" x 32")

- Used to store medium-sized products.
- Load capacity of up to 220 lb.
- Various heights available.












Cardboard boxes
Medium-sizedcardboard boxes can be stored directly without additional support (plastic boxes or trays) if they do not need to enter the warehouse again.

Even if the most used cardboard boxes have similar measures to plastic boxes, their variability, rigidity, and possible deformation mean that they require specific treatment.

Plastic or metal trays
Traysare usedto storeboxes and objects of varying dimensions, and are built specifically according to the product and the specific operations of each client. They can be made from plastic or metal.



Extraction system with forks to extract two boxes at the same time



2

Extraction systems

Different extraction systems can be installed in the cradle of the miniload. The system chosen will depend on the product, the number of units to be handled, and the movements that will be required.

The cradle can host one or two extraction systems.
The most frequent of these are indicated below:



Extraction system with forks (EP)
This is the simplest and most commonly used system. The fork enters through the bottom and extracts the box.

There are two types of model for single and double depth. There is also a model that can extract two boxes at the same time.




Details of the extraction system that combines forks with belts (EC).





Extraction system that combines forks with belts (EC)
With this system, the forks are activated by belts that push and pull the load.

It is a fast-paced dynamic system that can move one or two boxes at once, as it is possible to work on both sides of the racking unit.



Cradle with two extractors that carries four boxes at once.

Extraction system with side claws (EG)
Thisisasystem ofvertical forks with semi-detachable shafts that hold up cardboard boxes (up to two at once). When the shafts are in a horizontal position, they trap the boxes to extract or push them along.


These forks also facilitate the movement of boxes to change the side or depth on the racking on which they have been placed.



3
Models of stacker cranes

Eachwarehouse requirementdemands a different model of stacker crane.


There are three basic lines of stacker crane, each with different speeds and equipment depending on the services required.



The ML50
These vehicles are characterized by a slotted steel column that can handle up to 110 lb at a height of 30'. Basically, this range is designed for high productivity.



The ML100
These vehicles have a maximum height of 39', and can carry up to two 110 lb boxes.



The MLB
These stacker cranes can exceed 66' in height, and carry up to four 110 lbboxes with two pieces of equipment for double extraction.





4

Single or double depth

This type ofwarehouse canbe built to hold one box (single depth) or two boxes (double depth) on each side of the aisle.

Single depth

-Oneboxperlocation on racking.

- Maximum speed of entries and extraction of boxes.

- Ideal for warehouses where priority is placed on the speedofthesystem, ratherthantotalwarehouse capacity.

- There is directaccessto all boxes. Therefore, it is mainly used when the products stored are all of the same category and consumed in the same quantities, or when there is more than one box per SKU.





Warehouse with double depth

Double depth

-Twolevelsofdepth in each location ontheracking.

- Maximum box warehouse capacity.

- For companies that seek a perfect balance between warehouse capacity and speed of handling.

There is direct access to the boxes in front, while those behind them require the ones in front to be moved before they can be accessed. While at first this would appear to be a disadvantage, this is not the case in warehouses with a mix of A, B, and C products (“A” products being high-consumption products, “B” products medium-consumption, and “C” products low-consumption) since:

- The reserve box with product A is placed in the box behind the front row.

- Product C can be placed in the second position.

- Given that it is usually known what will be prepared beforehand, during idle-time products can be repositioned so that those that will leave first are placed in front. It also allows renovations of boxes to be carried out outside of business hours.

- Capacity per aisle is doubled.



5

One or more aisles

Automated warehouses for boxes, which are of variable height and length, can consist of one or more aisles, depending on the exact warehouse capacity, the dimensions of the warehouse, and the required number of movements.




6

One stacker crane per aisle

The most commonarrangement is to install one stacker crane per aisle. The model and number of extractors will depend on the load unit and the needs of the client.





Automated warehouse for boxes with nine aisles served by a single stacker crane.

1. Shuttle
2. Transfer bridge

7

One stacker crane for several aisles

Inwarehouseswith little movement, one stacker crane for several aisles is sufficient. To change aisles, there is a transfer bridge located at the rear of the warehouse.

To move boxes to the various picking positions, a shuttle in the front could be sufficient, rather than a circuit of conveyors.



Details of a shuttle (1).



Details of a transfer bridge (2).

8

Several stacker cranes per aisle

Two stacker cranes that move in the same lane in the same aisle can be installed, albeit with certain restrictions.


Another solution is to position two or more stacker cranes in height, as shown in these images.

For this, the racking incorporates auxiliary structures such as elevated aisles, with support and guide lanes along which stacker cranes move.

The number and measurements of stacker cranes are determined by the height of the warehouse and the number of movements required by the system.

The installation of more than one stacker crane in height multiplies the number of movements. This, when combined with the correct choice of model of machine, will result in an increase in the capacity of locations, as well as an increase in flows. Therefore, it is a very suitable solution for warehouses considered high-performance, or when the warehouse is used for sequencing purposes.


1. Warehouse racking 2. Lower level miniload 3. Upper level miniload 4. Intermediate structure 5. Lower level input conveyors 6. Upper level input conveyors 7. Lower level output conveyors 8. Upper level output conveyors 9. General collector



Goods that come from the production or reception areas are sent to the appropriate level using forklift trucks that send them to separate channels with sloping sections.

In the image, there are separate entry and exit channels that prevent products from being mixed together and can result in very high flows.

Example of an automated warehouse for boxes with eight stacker cranes: four to service aisles on the top floor, and four to service aisles on the lower floor.



Lateral view of the warehouse, with two stacker cranes in height.



9

Picking and replenishment positions


Eachwarehouse solution hasa specific header solution and, therefore, a particular picking position solution.

With a single aisle, there are two header options: frontal and lateral.

Frontal header

This is a U-shaped circuit located at the end of the racking. The operator carries out the various functions at the front, where the support equipment (screen, barcode reader, confirmation buttons, emergency stop button, control of loading gauge, etc.) is located.

Goods are replenished in the picking position itself.




Details of a frontal header



Lateral header
In thiscase,the circuit is also U-shaped but positioned laterally to the racking.

This solution is ideal when better use must be made of the length available, or when two stacker cranes are working in the same aisle.






Details of a lateral header




In warehouses with two or more aisles, the number and form of picking positions depend on the number of picking operations to be carried out and on the procedure used in the preparation of orders. This is also true of operations to replenish stock, which can be carried out in the same position or in some other location.

Examples of picking positions:




Two aisles and two separate picking positions
In this case, two warehouses with one aisle are combined. Each position only receives boxes stored in one aisle. Working with just one operator is a viable option.

Goods are replenished in the picking position itself.



Two aisles with one picking position
A unidirectional cross conveyor belt connects the different input and output conveyors to the picking position. Goods can be replenished in the picking position itself or via an additional conveyor connected to a production center or replenishment position.




Two aisles and two picking positions
Twocross conveyor belts areinstalled to allow the inward and outward movement of boxes, both from the aisles and from picking positions.

This solution is only valid if the two stacker cranes can supply the number of boxes required by each operator.

As with the previous solution, goods can be replenished in the picking position itself or via an additional conveyor.

Numerous aisles and numerous picking positions
Whenthere are more than twoaisles and more than one picking position, a minimum of two cross conveyor belts are required to connect the input and output conveyors in the warehouse to the picking positions.

A specific position for replenishment operations is also required. This position can be in the same area or in another part of the building connected to the warehouse using roller co nveyo r s .








Picking on lateral live storage racking
Whena large number of SKUs are accessed on a constant basis, an optimal solution is to install live storage racking on the lower levels, positioned laterally and able to handle a depth of two or more boxes.

The reserve is situated at the top of the warehouse. The stacker crane replaces channels as the boxes are emptied.

While working with this system, pick to light devices and conveyors can be installed. These devices make the work of the operator easier in order to improve their performance.

The image below illustrates a solution with two aisles: one single depth and one double depth. One of the double-depth live storage racking laterals has picking channels and a conveyor, while at the front there is a header with two picking positions for preparing SKUs consumed in smaller volumes.

The repositioning is carried out at an independent point.



A two-aisle automated warehouse for boxes with live storage racking on one side.





Large-scale frontal picking
How a warehouse operates is determined by the number of picking positions, stacker cranes, lines to prepare, and orders prepared by each operator.

Boxes can arrive at picking positions in an intermittent manner, thereby there is a need for an accumulation conveyor in each position. Nevertheless, said goods may need to arrive in a certain sequence in order to avoid down time in operations. Each warehouse will require a specific project, designed to the requisites of the client.

The example in this illustration shows a warehouse with nine double-cradle miniloads, seven picking positions, a position for replenishing stock from the pallet area, and three conveyor circuits. With this arrangement, boxes destined for picking positions and the warehouse and boxes containing orders that have already been prepared are not mixed together.

A general collector connects this warehouse to other work areas.





Details of picking position

Warehouse with nine double-cradle miniloads, seven picking positions, a position for replenishing stock from the pallet area, and three conveyor circuits.


1. Warehouse for boxes
2. Stacker crane
3. Box fill position (supply)
4. Elevator
5. Picking position
5.1. Output conveyor to picking with accumulator
5.2. Semi-detachable ergonomic conveyor
5.3. Return conveyor
5.4. Boxes for orders
5.5. Conveyor for prepared orders
5.6. Boxes made for orders
6. Level of conveyors for dispatches





Picking positions in annexed areas
Pickingpositionscan be locatedin annexed areas, fitting out the space they would occupy if they were located in the front as a warehouse.

This type of solution facilitates future growth, in particular in picking positions. It also doubles the size of the warehouse, leaving the common conveyor area in the middle and each section of the warehouse on both sides.



Picking positions on the side on the automated warehouse for boxes.






Picking positions can also be installed in elevated areas. By installing them in elevated areas, the benefits of placing picking positions in annexed areas are retained and best use is made of the height of the warehouse.

The illustration below shows a warehouse with four picking positions on an elevated floor. The lower part is used as a classification and dispatch area. The conveyors on both floors are connected by an elevator.

1. Automated warehouse for boxes
2. Stacker crane
3. Picking positions
4. Elevator
5. Classification area



Automated warehouse with picking positions on an elevated floor.






Automated warehouse for boxes to supply a sorter
Theexample seen inthis illustration, a warehouse for cardboard boxes operated by 12 double stacker cranes, allows cardboard boxes to be stored directly with their goods inside. This is common in the textile and accessories sector.

When the time is right, the cardboard boxes are sent to the picking positions. The product is then extracted from inside the boxes and deposited loose in a classification sorter with accumulation cells. Each cell relates to an order, with the goods deposited automatically into the appropriate cell.

In this case, the sorter is a never-ending circuit of shuttles that form a chain. Each shuttle has a mobile horizontal band that, at precisely the right moment, moves the goods left or right to deposit them in the appropriate cell. Support equipment helps make the work of the various operators involved easier.

Orders prepared in the cells of the sorter are inserted into cardboard boxes, which are sent to the sealing and control section on the conveyors. Finally, these boxes are sent to the route classifiers installed in the dispatch bays.


For more information on sorters, go to pages 50-53.




1. Receipt of goods
2. Extendable conveyor
3. Quality control and reconditioning
4. Automated warehouse for boxes with stacker cranes
5. Box conveyor circuit
6. Area for insertion of individual units
7. Order classification sorter
8. Cells for the preparation of orders
9. Sealing and control section
10. Supply of empty boxes
11. Route classification
12. Dispatches







Automated warehouse for boxes provided by a sorter.



Automated warehouse for cardboard boxes with side entrance and exit.

10


Role as buffer

Miniloads canbe warehouses that regulate between different production areas, provided that they handle complete units. There are no picking positions.

In this case, two conveyors (one input, one output) connect the warehouse to the different areas.

Goods can enter and leave the warehouse via the front or through the sides, as shown in the images here.

Any type of stacker crane can operate in a warehouse that acts as a buffer. However, those used most frequently are high-performance stacker cranes, which can also be used as sequencers.



Automated warehouse for plastic boxes with front entrance and exit.

Another buffer solution is to install live pallet racking as a warehouse.

Boxes enter through one side of the channels, gathered, and are extracted through the other side when required.

Two stacker cranes (one on each side) fill and empty the warehouse.




11

Working temperatures

Some products requirecontrolled temperatures, with some requiring even temperatures below 32ºF (freezing chamber).


In these cases, the warehouse is insulated to prevent a loss of temperature and, therefore, saving energy.

In temperatures below zero, picking positions are located in annexed areas.



Automated warehouse for boxes in cold chamber with picking positions in an annexed area.

1. Medium-sized cold chamber
2. Racking
3. Stacker cranes
4. Input and output conveyors
5. Picking positions
6. Elevator
7. Annexed picking area (optional)
8. Order consolidation area




Miniload combined with different load units and diverse warehouse systems.

12

Combination with other warehouse systems

Different goodsandloadunitsthat require particular treatment can be kept in a single warehouse.

Furthermore, there can be great variation in the rate of consumption of these goods. As a result, the procedure will require a different application in each case.



1. Automated warehouse for boxes
2. Picking header
3. Box conveyor circuit
4. Vertical warehouse
5. Automated warehouse for pallets
6. Pallet conveyor circuit
7. Picking position on pallet and replenishment of automated warehouse for boxes
8. Conventional warehouse for pallets
9. Compact warehouse for pallets
10. Classification sorters
11. Consolidation area
12. Loading bay

Thus, different warehouse systems are often combined, with simpler or more complex solutions, depending on the requirements of the client.

Example 1


In this example, there is an automated warehouse for boxes incorporated into a larger warehouse. It consists of a compact pallet storage area for products of mass consumption, a conventional racking unit area served by trilateral turret trucks to store varied medium-sized goods, which allows orders to be prepared directly on the pallet or whole pallets to be dispatched, and an automated warehouse for pallets for reserve and large products. In addition, these areas have three automated Clasimat vertical warehouses for small components with order preparation and replenishment areas and a conveyor circuit, a classification sorter, a consolidation area, and loading bays.

It also has Easy WMS warehouse management software, which manages all areas of the warehouse in an integrated manner.



Example 2
Inthis example, there is an automated warehouse for boxes integrated with other picking warehouses (one with conventional racking and another with live pallet racking). All are connected by a circuit of box conveyors and elevators that, in turn, is connected with pallet conveyors and depalletizing posts, one of which is fully automated.

"A" products (products with high levels of consumption), "B" products (medium level of consumption) and "C" products (those consumed in small volumes) are stored in a single warehouse. According to the 80/20 principle (80% of consumption volumes is accounted for by 20% of SKUs, while the other 20% of consumption is accounted for by the other 80% of SKUs), close to 15% of SKUs could be "A" products, 35% "B" products, and 50% "C" products.



Automated warehouse for boxes integrated with other picking warehouses and connected by a system of conveyors.





Thus, according to what is stated here, it is logical to store each type of product with a different storage system, where the size of the warehouse so allows.

In the example in the image on the left, "A" products would be stored on live pallet racking, possibly using pick to light systems to improve performance, as this would result in more lines for the preparation of orders. "C" products would be on the conventional picking racking, while "B" products would be located on the miniloads.

A number of "B" products can be extracted frequently and, while they are not "A" products, it could be beneficial to store them in this system. For these products, there are sideways live pallet channels that facilitate picking. All other products are extracted from normal picking positions in the header.

When orders are prepared in different areas, there is a consolidation area. It is important to analyze how goods are sent from reception areas as well as from preparation areas. In this example, they are sent on roller or band conveyors, as well as vertical elevators that connect the two floors.


1. Automated warehouse for boxes
2. Conventional picking warehouse (operated using shuttles with IT support equipment)
3. Live pallet picking warehouse with pick to light
4. Automated conveyor circuit and box elevation
5. Quality control
6. Unloading bay
7. Automated pallet conveyor circuit
8. Depalletizer (automatic and manual)
9. Lateral picking in automated warehouse for boxes
10. Picking in the header of the automated warehouse for boxes



Example 3
In thisexample, there is a warehouse in which products have been divided into different areas. The most appropriate system is chosen based on the dimensions and typology of the product, the quantity to be stored, and picking and safety requirements.

Each area of the warehouse is strategically located, depending on the flows of movements and the size of the product.

There are various conventional warehouse systems and three automated warehouse systems. The latter includes a self-supporting warehouse for pallets, which has a picking position, four automated Clasimat vertical warehouses for components, and a single depth




1. Automated warehouse for boxes
2. Automated warehouse for pallets
3. Vertical warehouses
4. Irregular large goods
5. Warehouse for reels
6. Warehouse for bulky goods
7. Profile warehouse
8. Battery charging for turret trucks
9. Reception area
10. Consolidation area
11. Loading and unloading bay

miniload with a lateral picking position for medium-sized products.

Orders are consolidated in a common area used by the three systems to later send them to the appropriate dispatching channel, depending on the order or route.

The Mecalux Easy WMS management software program controls all functions performed in any part of the warehouse.




Automated warehouse for boxes combined with other automated and traditional systems.

Example 4
Inthis example, there is another possible solution for an automated warehouse for boxes combined with live pallet racking and an order sorter.


“B” and “C” products are located in the automated warehouse, while “A” products are positioned in live pallet warehouse. The products prepared in both areas are automatically carried to an order sorter, where they are consolidated and identified by operators.

Live pallet racking incorporates pick to light systems for the paperless preparation of orders, and roller conveyors to facilitate the preparation and transportation of the boxes.

There is a position for replenishing orders for the automated warehouse for boxes in an area separate from the picking positions, with direct exits for empty boxes and an input conveyor to the header.







Automated warehouse for boxes combined with live pallet racking and an order sorter.

1. Automated warehouse for boxes
2. Header picking position
3. Position for replenishing automated warehouse for boxes
4. Output of empty boxes with accumulation
5. Input of replenishment boxes
6. Live pallet racking with pick to light
7. Replenishment for live pallet racking
8. Goods to replenish automated warehouse for boxes
9. Goods to replenish live pallet racking
10. Conveyors for prepared orders
11. Order sorter
12. Consolidation of orders



13

Support equipment for the preparation of orders

There are different support equipment for the preparation of orders. The most common of these are as follows:

Preparation of orders with the 'picktolight' system

This is an automated system built into the WMS (warehouse management system) for the paperless preparation of orders.

On the racking unit or levels there are digital screens that light up, indicating the number of units to be extracted if the order to be prepared contains a product in that location.

The operator follows the instructions on the screen and once the extraction of that SKU has completed, presses the confirmation button that turns off the light and validates the picking action.




This system speeds up the preparation of orders and significantly reduces the number of errors made.

This system is often found in automated warehouses for boxes, in particular at the side exits of the live pallet picking system.









Preparation of orders with the 'put to light' system
This is the same system as pick to light, but goods are deposited in the position where the digital screen is illuminated. In general, goods are deposited in fixed picking positions when a number of orders are being prepared at the same time.

Shuttles with 'put to light' systems
It iscommon tocombinethem in high-performance picking positions, or when a number of orders are being prepared at the same time, starting at live pallet racking where pick to light systems and shuttles go along with put to light systems.

Shuttles with put to light systems can carry a number of orders at once. An electronic controller connected by radio frequency to the WMS computer transmits the different signals.

This system allows orders on conventional racking and on live pallet side racking in automated warehouses for boxes.

14

Automatic classification sorter


Inthe previous pages, we saw different ways of preparing orders, collecting products from within a box and putting them in a pigeon hole or a box for the preparation of orders. With these systems, there is a given number of preparation lines determined as a function of the system chosen and the support equipment available.

When a large number of orders needs to be prepared at the same time, more agile systems such as the cross-belt classification sorter are required. These



are shuttles joined together that form a never-ending chain on a closed circuit. Each shuttle carries one unit, which is unloaded into a particular cell that contains all products for a single order. Thus, the tables used to prepare orders become positions where goods are loaded into the sorter.





Side view of classification cells

Details of a shuttle






1. Loading positions
2. Sorter circuit 3. Classification cells 4. Packing boxes 5. Box conveyors


Horizontal sorter
Thereare two typesof sorter: horizontal and vertical. This page contains the horizontal sorter, which can prepare twice as many orders with the same number of shuttles as the vertical sorter.



Horizontal sorter



Vertical sorter
The verticalsorter is more compact and occupies less space, even though it requires more shuttles than the horizontal sorter. The number of shuttles will depend on the number of orders being prepared at any one time.



Section of a frontal view of the vertical sorter


This type of sorter is suitable when only a small number of orders is being prepared, or when the space required by the horizontal sorter is not available.

As can be seen in the images, the system is very compact. Internal conveyors can be used for boxes with prepared orders.





1. Loading positions 2. Classification sorter 3. Classification cells 4. Packing boxes 5. Box conveyors



Vertical sorter

Section of a lateral view of the vertical sorter



Easy WMS Warehouse Management Software
The brain of the installation



Easy WMS is a warehouse management software (WMS) developed and constantly updated by the Mecalux Software Solutions division, comprising more than 150 full time engineers.

Easy WMS ensures correct operation and control of installations, coordinating the movement of goods from origin to destination to achieve maximum efficiency. It also handles full warehouse operations to integrate with customer systems, because it has standard communication interfaces with the leading ERPs on the market.

To facilitate integration of the software in warehouses of every kind and size, Easy WMS has several modules that provide great flexibility and a high degree of customization. It offers two types of architecture: cloud-based (SaaS) and on-premises.



Here are some of the benefits of automated warehouse management with Easy WMS:

Enhances productivity and lessens the number of operations.

Storage capacity improved by up to 40%, maximizing thespace occupied by goods in the warehouse.

Increases the speed of order preparation and dispatch.

Reduction of up to 99% oferrorsinthe inbound and outbound processing of material.

Control and optimization of stock.

Real-time inventory

andtraceabilityof goods.

Logistics cost reduction:

optimizeshuman resources and handling costs.

Multi-proprietor, multi-warehouse and **multilingual** functionalities.

Ability to adapt to new market requirements or trends, such as e-commerce.

Improved document management.

For more information, request the Easy WMS catalog or contact the sales department to ask for a demonstration or obligation-free advice.





The advantages of automation

As can be seen, there is a wide variety of possible solutions when it comes to building automated warehouses for boxes. The in-depth analysis of the needs of each client will result in the optimal system being chosen.


Special emphasis has also been placed on usual arrangements, which is to combine elements of different systems, each best suited to a specific type of product and operation.


Irrespective of the solution chosen, the highest degree of automation in management and appropriate software will be required to control the flows and needs of the warehouse.


Furthermore, automated warehouses for boxes automate the movements of the warehouse, since machines move about with the goods in question while the operator remains in their position. The more automated and flexible the picking position and the more efficient the support equipment chosen, the better the ultimate performance of the warehouse.


With automated warehouses for boxes, one can:


- **Optimize space and height**.
- **Maximize productivity** in picking operations.
- **Automate entry and exit operations**.
- Ensure **perfect control** of stock.
- **Eliminate errors** that result from manual handling in the warehouse.
- **Control and update inventory management**.












This involves an improvement in the quality of service, as well as a rapid amortization of investment.

The Mecalux technical departments will be able to advise you on how and when to automate your warehouse. Its experience in storage solutions and intralogistics, the powerful simulation equipment, and variety of products available will enable you to find the optimal solution for each type of warehouse.

Example of simulation of an automated warehouse for boxes.

International presence



4 technological centers

(1) In Barcelona (Spain), an R&D centerfor **engineering projects** and **automatic equipment**.

(2) In Gijón (Spain), a development center for **warehouse management software and related products**.

(3) In Gliwice (Poland), a research center for **automated systems**.

(4) In Chicago, an R&D center for **engineering projects**.

Gliwice plant (1)
(POLAND)
575,800 sq ft



Barcelona plant (1)
(SPA I N)
430,500 sq ft

Sales network

Production centers

EASY FIT STORAGE
SOLUTIONS



EASY FIT STORAGE
SOLUTIONS